

CITY COUNCIL OF THE CITY OF OXNARD
ORDINANCE NO. _____

AN ORDINANCE OF THE CITY COUNCIL OF THE CITY OF OXNARD REPEALING AND REENACTING ARTICLES I THROUGH IX, XIV, AND XV OF CHAPTER 14 OF THE OXNARD CITY CODE, RENUMBERING ARTICLES, X, XI, XII, AND XIII OF CHAPTER 14 OF THE OXNARD CITY CODE TO ARTICLES XX, XXI, XXII, AND XXIII RESPECTIVELY, AND ADDING ARTICLES X THROUGH XIII AND ARTICLES XVI THROUGH XIX TO CHAPTER 14 OF THE OXNARD CITY CODE PERTAINING TO THE CALIFORNIA BUILDING CODE, CALIFORNIA RESIDENTIAL CODE, CALIFORNIA GREEN BUILDING STANDARDS CODE, INTERNATIONAL PROPERTY MAINTENANCE CODE, UNIFORM CODE FOR THE ABATEMENT OF DANGEROUS BUILDINGS, CALIFORNIA HISTORICAL BUILDING CODE, CALIFORNIA ELECTRICAL CODE, CALIFORNIA EXISTING BUILDINGS CODE, CALIFORNIA MECHANICAL CODE, CALIFORNIA REFERENCED STANDARDS CODE, CALIFORNIA PLUMBING CODE, FIRE CODES, FIRE SPRINKLERS, REPORT OF BUILDING RECORDS, MOVING OF BUILDINGS, SWIMMING POOL PROVISIONS, AND BEACH CONSTRUCTION.

The City Council of the City of Oxnard does ordain as follows:

PART 1. Articles I through IX, XIV, and XV of Chapter 14 of the Oxnard City Code are hereby repealed.

Article X of Chapter 14 of the Oxnard City Code, REPORT OF BUILDING RECORDS, is hereby renumbered to Article XX of Chapter 14 of the Oxnard City Code.

Article XI of Chapter 14 of the Oxnard City Code, MOVING OF BUILDINGS, is hereby renumbered to Article XXI of Chapter 14 of the Oxnard City Code.

Article XII of Chapter 14 of the Oxnard City Code, SWIMMING POOL PROVISIONS, is hereby renumbered to Article XXII of Chapter 14 of the Oxnard City Code.

Article XIII of Chapter 14 of the Oxnard City Code, BEACH CONSTRUCTION, is hereby renumbered to Article XXIII of Chapter 14 of the Oxnard City Code..

Articles X through XIII and Articles XVI through XIX are hereby added to Chapter 14 of the Oxnard City Code.

PART 2. The following acronyms are used in this ordinance to clarify the sections of the City Code being added or amended.

| | |
|----------------------------|--|
| ACI-318 | American Concrete Institute – Building Code Requirements for Structural Concrete, 2005 Edition. |
| AF&PA SDPWS | American Forest & Paper Association – Special Design Provisions for Wind and Seismic |
| ANSI | American National Standards Institute |
| ASCE-7 | American Society of Civil Engineers – Minimum Design Loads for Buildings and Other Structures, 2005 Edition. |
| CABO | Council of American Building Officials |
| CAC | California Administrative Code [Title 24, Part 1 of the California Code of Regulations (C.C.R.)] |
| CBC | California Building Code [Title 24, Part 2 of the California Code of Regulations (C.C.R.)] |
| CBSC | California Building Standards Commission |
| CEBC | California Existing Building Code [Title 24, Part 10 of the California Code of Regulations (C.C.R.)] |
| CEC | California Electrical Code [Title 24, Part 3 of the California Code of Regulations (C.C.R.)] |
| CALGreen | California Green Building Standards Code [Title 24, Part 11 of the California Code of Regulations (C.C.R.)] |
| CFC | California Fire Code [Title 24, Part 9 of the California Code of Regulations (C.C.R.)] |
| CHBC | California Historical Building Code [Title 24, Part 8 of the California Code of Regulations (C.C.R.)] |
| CMC | California Mechanical Code [Title 24, Part 4 of the California Code of Regulations (C.C.R.)] |
| CPC | California Plumbing Code [Title 24, Part 5 of the California Code of Regulations (C.C.R.)] |
| CRC | California Residential Code [Title 24, Part 2.5 of the California Code of Regulations (C.C.R.)] |
| IAPMO | International Association of Plumbing and Mechanical Officials |
| NEC | National Electrical Code |

PART 3. Article I – (Reserved), Article II – California Building Code, Article III California Residential Code, Article IV – California Green Building Standards Code, Article V – Property Maintenance and Abatement Codes, Article VI – California Historical Building Code, Article VII - California Electrical Code, Article VIII – California Existing Buildings Code, Article IX - California Mechanical Code, Article X – California Referenced Standards Code, Article XI - California Plumbing Code, Article XII through and including Article XIV – (Reserved), Article XV – Fire Codes, Article XVI – Fire Sprinklers, and Article XVII through and including Article XIX – (Reserved) are hereby added to Chapter 14 of the Oxnard City Code to read as follows:

ARTICLE I. (RESERVED)

SEC. 14-1. (RESERVED)

ARTICLE II. CALIFORNIA BUILDING CODE

SEC. 14-2. CALIFORNIA BUILDING CODE ADOPTED.

The second part of twelve parts of the California Code of Regulations, Title 24, known as the California Building Code (“CBC”), 2010 Edition, including Appendices C, H, and J, as published by the International Code Council, 500 New Jersey Avenue, NW, 6th Floor, Washington, D.C. 20001, is hereby adopted by reference, subject to the amendments, additions, and deletions hereinafter set forth. One true copy of this code is on file in the office of the City Clerk and is available for public inspection as required by law.

SEC. 14-3. AMENDMENTS TO THE CBC.

(A) Chapter 1 Division II, Section 101.4.4: Amend Section 101.4.4 to read as follows:

101.4.4. Property Maintenance. The provisions of the Oxnard City Code shall apply to existing structures and premises; equipment and facilities; light, ventilation, space heating, sanitation, life and fire safety hazards; responsibility of owners, operators and occupants; and occupancy of existing premises and structures.

(B) Chapter 1 Division II, Section 103.1: Amend Section 103.1 to read as follows:

103.1. Creation of enforcement agency. The Building and Engineering Division of the Development Services Department is hereby created and the official in charge thereof shall be known as the building official.

(C) Chapter 1 Division II, Section 105.2: Amend Section 105.2, items 2 and 4, to read as follows:

Building:

2. Fences not over 6 feet high and masonry walls not over 3'-6" high as measured from the lowest finished grade to the top of the wall.
4. Retaining walls that are not over 3 feet in height measured from the bottom of the footing to the top of the wall, unless supporting a surcharge or impounding Class I, II, or II-A liquids.

(D) Chapter 1 Division II, Section 105.3.2: Amend Section 105.3.2, to read as follows:

105.3.2. Time limitation of application. An application for a permit for any proposed work shall be deemed to have been abandoned 180 days after the date of filing, unless such application has been pursued in good faith or a permit has been issued; except that the building official is authorized to grant one or more extensions of time for additional periods not exceeding 180 days each. The extension shall be requested in writing and justifiable cause demonstrated.

(E) Section 903.2: Amend Section 903.2 to read as follows:

Approved automatic sprinkler systems in new buildings and structures shall be provided in the location described in Sections 903.2.1 through 903.2.12 and as required in accordance with Chapter 14 of the Oxnard City Code, Article XVI.

(F) Section 1403.1: Amend Section 1403.1 to read as follows:

1403.1. General. The provisions of this section shall apply to exterior walls, wall coverings and components thereof. Additionally, balconies, landings, exterior stairways, occupied roofs and similar surfaces exposed to the weather and sealed underneath shall be waterproofed and sloped a minimum 1/4 unit vertical in 12 units horizontal (2% slope) for drainage. The weather-exposed areas with ceilings or horizontal projections not required to be sealed for fire resistive construction shall be provided with ventilation devices so as to provide adequate air movement to dry out any moisture infiltrating within the horizontal areas. Details and notes on ventilation devices shall be provided in the submittal drawings.

(G) Section 1505.1: Amend the first paragraph of Section 1505.1 to read as follows:

1505.1. General. The roof covering on any structure regulated by this code shall be a Class A or B roof covering. The roof covering assembly includes the roof deck, underlayment, interlayment, insulation, and covering which is assigned a roof covering classification. Roof coverings required to be listed by this section shall be tested in accordance with ASTM E 108 or UL 790. In addition, fire-retardant-treated wood roof coverings shall be tested in accordance with ASTM D 2928.

(H) Section 1510.1: Amend the first paragraph of Section 1510.1 to read as follows:

1510.1. General. All reroofing shall be constructed with Class A or B roofing and shall conform to the applicable provisions of Chapter 15 of this Code, or as approved by the building official.

(I) Section 1613.6.7: Equation 16-44 of Section 1613.6.7 is amended to read as follows:

$$\delta_M = C_d \delta_{max} \quad (\text{Eq. 16-44})$$

(J) Section 1613.8: Add Section 1613.8 to read as follows:

1613.8 Modification to ASCE 7 Section 12.11.2.2.3. ASCE 7 Section 12.11.2.2.3 is modified to read as follows:

12.11.2.2.3 Wood Diaphragms. In wood diaphragms, the continuous ties shall be in addition to the diaphragm sheathing. Anchorage shall not be accomplished by use of toe nails or nails subject to withdrawal nor shall wood ledgers or framing be used in cross-grain bending or cross-grain tension. The diaphragm sheathing shall not be considered effective as providing ties or struts required by this section.

For wood diaphragms supporting concrete or masonry walls, wood diaphragms shall comply with the following:

1. The spacing of continuous ties shall not exceed 40 feet. Added chords of diaphragms may be used to form sub-diaphragms to transmit the anchorage forces to the main continuous cross-ties.
2. The maximum diaphragm shear used to determine the depth of the sub-diaphragm shall not exceed 75% of the maximum diaphragm shear.

(K) Section 1613.9: Add Section 1613.9 to read as follows:

1613.9. Modify ASCE 7 Table 12.8-2 by adding the following:

| Structure Type | C_t | α |
|---|-------------------------------|----------|
| Eccentrically braced steel frames <u>and</u> buckling-restrained braced frames | 0.03 (0.0731) ^a | 0.75 |

(L) Section 1613.10: Equation 12.8-16 of ASCE 7 section 12.8.7 is amended to read as follows:

$$v = \frac{P_x \Delta I}{V_x h_{sx} C_d} \quad (\text{Eq. 12.8-16})$$

(M) Section 1704.4: Amend Section 1704.4 to read as follows:

1704.4 Concrete Construction. The special inspections and verifications for concrete construction shall be as required by this section and Table 1704.4.

EXCEPTIONS: Special inspection shall not be required for:

1. Isolated spread concrete footings of buildings three stories or less in height that are fully supported on earth or rock, where the structural design of the footing is based on a specified compressive strength, f'_c , no greater than 2,500 pounds per square inch (psi) (17.2 Mpa).
2. Continuous concrete footings supporting walls of buildings three stories or less in height that are fully supported on earth or rock where:
 - 2.1. The footings support walls of light-frame construction;
 - 2.2. The footings are designed in accordance with Table 1805.4.2; or
 - 2.3. The structural design of the footing is based on a specified compressive strength, f'_c , no greater than 2,500 pounds per square inch (psi) (17.2 Mpa), regardless of the compressive strength specified in the construction documents or used in the footing construction.
3. Nonstructural concrete slabs supported directly on the ground, including concrete patios, driveways and sidewalks

(N) Section 1707.3: Amend Section 1707.3, Exception, to read as follows:

Exception: Special inspection is not required for wood shear walls, shear panels and diaphragms, including nailing, bolting, anchoring and other fastening to other components of the seismic-force-resisting system, where either (1) the fastener spacing of the sheathing is more than 4 inches (102mm) on center (o.c.), or (2) the tabular values for

allowable shear from Tables 2306.2.1(1) and 2306.3 are reduced to seventy-five percent (75%).

(O) Section 1710.1: Amend Section 1710.1 to read as follows:

1710.1 General. Where required by the provisions of Section 1710.2 or 1710.3, the owner shall employ a structural observer to perform structural observations as defined in Section 1702. The structural observer shall be one of the following individuals:

1. The registered design professional responsible for the structural design, or
2. A registered design professional designated by the registered design professional responsible for the structural design.

Prior to the commencement of observations, the structural observer shall submit to the building official a written statement identifying the frequency and extent of structural observations.

At the conclusion of the work included in the permit, the structural observer shall submit a final report which states that all observed deficiencies have been resolved, prior to acceptance of the work by the building official.

(P) Section 1803.2: Amend the first paragraph of Section 1803.2 to read as follows:

1803.2. Investigation required. Geotechnical investigations shall be conducted in accordance with Sections 1803.3 through 1803.5. Whenever unusual soil conditions are found which justify a special site investigation to determine soil stability or questionable adequacy of the overall building site, the building official may require that the owner obtain a special geological, hydrological, soil gas profile, soil chemical analysis, soils contamination, or other report as may be deemed appropriate. The investigation shall be conducted by trained and experienced professionals licensed by the State of California to prepare such evaluations, recommendations, and reports.

(Q) Section 1804.3: Amend Section 1804.3 to read as follows:

1804.3. General Site Grading and Drainage. Provisions shall be made for the control and drainage of surface water around buildings. Concentrated drainage such as rainwater from gutters and downspouts, scuppers, and roof valleys shall be diverted away from building foundations by means of concrete splash blocks or other approved non-erosive devices. Unless an alternate design is approved by the building official, under floor access crawl holes shall be provided with curbs extending not less than six (6) inches above adjacent grade to prevent surface water from entering the under floor area.

Gutters and Downspouts - when buildings are located on expansive soil having an expansion index greater than 50, gutters, downspouts, piping, and/or other non-erosive devices shall be provided to collect and conduct rainwater to a street, storm drain, or other approved watercourse or disposal area.

Lot Drainage - All lots shall be graded so that they drain to the street or public way on which they abut or shall be provided with approved drainage devices. Minimum gradient of all lots shall comply with the following:

1. Pervious surfaces -- 1/8 inch per foot (1 percent slope).
2. Asphalt surfaces -- 1/16 inch per foot (1/2 percent slope).
3. Concrete surfaces -- 1/32 inch per foot (1/4 percent slope).

In rural areas where curbs or gutters have not been installed, drainage design plans shall be submitted for approval by the building official.

(R) Section 1808.7.4 : Amend Section 1808.7.4 to read as follows:

1808.7.4. Foundation and Slab Elevation. The top of any exterior foundation or finished floor slab, shall extend 25 inches above the elevation of the lowest adjacent street gutter. Beginning at an elevation eight (8) inches below the top of foundation or floor slab, a minimum 2 percent (2%) slope away from the foundation or floor slab shall be maintained around its perimeter for a minimum distance of four (4) feet for side yards and ten (10) feet for front and rear yards. The building official may approve alternate elevations, provided it can be demonstrated that required drainage to a safe point of discharge and away from the foundation is provided at all locations on the site.

(S) Section 1908.1: Amend Section 1908.1 to read as follows:

1908.1. General. The text of ACI 318 shall be modified as indicated in Sections 1908.1.1 through 1908.1.9.

(T) Section 1908.1.8: Amend Section 1908.1.8 to read as follows:

1908.1.8. Section 22.10 of ACI 318 is not adopted. It is replaced with the following:

22.10 – Plain concrete in structures assigned to Seismic Design Category C, D, E, or F.

22.10.1 Structures assigned to Seismic Design Category C, D, E, or F shall not have elements of structural plan concrete, except as follows.

(a) Concrete used for fill with a minimum cement content of two (2) sacks of Portland cement per cubic yard.

(b) Isolated footings of plain concrete supporting pedestals or columns are permitted, provided the projection of the footing beyond the face of the supported member does not exceed the footing thickness.

(c) In detached one- and two-family dwellings three stories or less in height and constructed with stud-bearing walls, plain concrete footings having a

total area of longitudinal reinforcing steel of not less than 0.002 times the gross cross-sectional area of the footing, with at least two continuous longitudinal reinforcing bars not smaller than No. 4 are permitted. In addition, where the foundation system consists of a plain concrete footing and a plain concrete stemwall, an additional longitudinal reinforcing bar not smaller than No. 4 shall be provided at the top of the stemwall, and vertical bars not less than No.4 shall be placed in the stemwall at 24" on center, with a standard 90 degree hook into the footing.

(U) Section 1908.1.11: Add Section 1908.1.11 to read as follows:

1908.1.11. Modify ACI 318 Section 21.6.4.1 to read as follows:

Where the calculated point of contraflexure is not within the middle half of the member clear height, provide transverse reinforcement as specified in ACI 318 Sections 21.6.4.1, items (a) through (c), over the full height off the member.

(V) Section 1908.1.12: Add Section 1908.1.12 to read as follows:

1908.1.12. Modify ACI 318 by adding Section 21.6.4.8 to read as follows:

21.6.4.8 – At any section where the design strength, ϕP_n , of the column is less than the sum of the shears V_e computed in accordance with ACI 318 Sections 21.3.4.1 and 21.4.5.1 for all the beams framing into the column above the level under consideration, transverse reinforcement as specified in ACI 318 Sections 21.4.4.1 through 21.4.4.3 shall be provided. For beams framing into opposite sides of the column, the moment components may be assumed to be of opposite sign. For the determination of the design strength, ϕP_n , of the column, these moments may be assumed to result from the deformation of the frame in any one principal axis.

(W) Section 1908.1.13: Add Section 1908.1.13 to read as follows:

1908.1.13. Modify ACI 318 by adding Section 21.9.4.6 to read as follows:

21.9.4.6 – Walls and portions of walls with $P_u > 0.35P_o$ shall not be considered to contribute to the calculated strength of the structure for resisting earthquake-induced forces. Such walls shall conform to the requirements of Section 1631.2, Item 4, and ACI 318 Section 21.11.

(X) Section 1908.1.14: Add Section 1908.1.14 to read as follows:

1908.1.14. Modify ACI 318 section 21.11.6 by adding the following:

Collector and boundary elements in topping slabs placed over precast floor and roof elements shall not be less than 3 inches (76mm) or $6 d_b$ thick, where d_b is the diameter of the largest reinforcement in the topping slab.

(Y) Section 2204.1.1: Add Section 2204.1.1 to read as follows:

2204.1.1. Consumables for welding.

2204.1.1.1 Seismic Force Resisting System (SFRS) welds. All welds used in members and connections in the SFRS shall be made with filler metals meeting the requirements specified in AWS D1.8 Clause 6.3. ASW D1.8 Clauses 6.3.5, 6.3.6, 6.3.7, and 6.3.8 shall apply only to demand critical welds.

2204.1.1.2 Demand critical welds. Where welds are designated as demand critical, they shall be made with filler metals meeting the requirements specified in AWS D1.3 Clause 6.3.

(Z) Section 2205.4: AISC 341, Part I, Section 13.2 Members. Add Section 13.2f to read as follows:

13.2f Member Types.

The use of rectangular HSS are not permitted for bracing members, unless filled solid with cement grout having a minimum compressive strength of 3,000 psi at 29 days. The effects of composite action in the filled composite brace shall be considered in the sectional properties of the system where it results in the more severe loading condition or detailing.

(AA) Section 2306.2.1: Amend Section 2306.2.1 to read as follows:

2306.2.1 Wood structural panel diaphragms.

Wood structural panel diaphragms shall be designed and constructed in accordance with AF&PA SDPWS. Wood structural panel diaphragms are permitted to resist horizontal forces using the allowable shear capacities set forth in Table 2306.2.1(1) or 2306.2.1(2). The allowable shear capacities in Tables 2306.2.1(1) and 2306.2.1(2) are permitted to be increased 40 percent for wind design.

Wood structural panel diaphragms using staples as fasteners shall not be permitted for structures assigned to Seismic Design Category D, E, or F.

Exception: Staples may be used for wood structural panel diaphragms, when the allowable shear values are substantiated by cyclic testing and approved by the building official.

Wood structural panel sheathing used as part of the seismic-force-resisting system shall be applied directly to framing members.

Exception: Wood structural panel sheathing in a horizontal diaphragm is permitted to be fastened over solid lumber planking or laminated decking, provided the panel joints and lumber planking or laminated decking joints do not coincide.

(BB) Section 2306.3: Amend Section 2306.3 to read as follows:

2306.3 Wood structural panel shear walls.

Wood structural panel shearwalls shall be designed and constructed in accordance with AF&PA SDPWS. Wood structural panel shearwalls are permitted to resist horizontal forces using the allowable capacities set forth in Table 2306.3. The allowable capacities in Table 2306.3 are permitted to be increased 40 percent for wind design.

Wood structural panel shear walls used to resist seismic forces in structures assigned to Seismic Design Category D, E, or F shall not be less than 4 feet by 8 feet (1219 mm by 2438 mm), except at boundaries and at changes in framing. Wood structural panel thickness for shear walls shall not be less than 3/8 inch thick and studs shall not be spaced at more than 16 inches on center.

The maximum allowable shear value for three-ply plywood resisting seismic forces in structures assigned to Seismic Design Category D, E, or F is 200 pounds per foot (2.92 kn/m). Nails shall be placed not less than 1/2 inch (12.7 mm) in from the panel edges and not less than 3/8 inch (9.5mm) from the edge of the connecting members for shear greater than 350 pounds per foot (5.11kN/m). Nails shall be placed not less than 3/8 inch (9.5 mm) from panel edges and not less than 1/4 inch (6.4 mm) from the edge of the connecting members for shears of 350 pounds per foot (5.11kN/m) or less.

Wood structural panel shear walls using staples as fasteners shall not be permitted for structures assigned to Seismic Design Category D, E, or F.

Exception: Staples may be used for wood structural panel shear walls, when the allowable shear values are substantiated by cyclic testing and approved by the building official.

Wood structural panel shear walls used to resist seismic forces in structures assigned to Seismic Design Category D, E, or F shall be applied directly to framing members.

(CC) Section 2306.7: Add Section 2306.7 to read as follows:

2306.7 Shear walls sheathed with other materials.

Shear walls sheathed with portland cement plaster, gypsum lath, gypsum sheathing or gypsum board shall be designed and constructed in accordance with AF&PA SDPWS. Shear walls sheathed with these materials are permitted to resist horizontal forces using the allowable shear capacities set forth in Table 2306.7. Shear walls sheathed with portland cement plaster, gypsum lath, gypsum sheathing or gypsum board shall not be used to resist seismic forces in structures assigned to Seismic Design Category E or F.

Exception: [DSA/SS, DSA/SS-CC, and OSHPD 1, 2 & 4]

Shear walls sheathed with portland cement plaster, gypsum lath, gypsum sheathing or gypsum board shall not be used to resist seismic forces in structures assigned to Seismic Design Category D.

Shear walls sheathed with portland cement plaster, gypsum lath, gypsum sheathing or gypsum board shall not be used below the top level in a multi-level building for structures assigned to Seismic Design Category D.

In Seismic Design Category D, the allowable seismic shear values set forth in Table 2306.7 shall be reduced as follows:

1. Maximum allowable shear value for lath and portland cement plaster shall not exceed 90 plf.
2. Maximum allowable shear value for gypsum shall not exceed 30 plf.

(DD) Appendix Chapter J, Section J103.2, Exception 1: Amend Appendix Chapter J, Section J103.2, Exception 1, to read as follows:

1. Grading in an isolated, self-contained area, provided there is no danger to the public, the total quantity of graded soil does not exceed 150 cubic yards, and that such grading will not adversely affect adjoining properties.

(EE) Appendix Chapter J, Section J103.2, Exception 8: Amend Appendix Chapter J, Section J103.2, by adding Exception 8 to read as follows:

8. An excavation which (1) is less than 2 feet (610mm) in depth, or (2) which does not create a cut slope greater than 5 feet (1524mm) in height and steeper than 1 unit vertical in 1-1/2 units horizontal (66.7% slope) and does not interfere with a drainage course.

(FF) Appendix Chapter J, Section J104.1: Amend Appendix Chapter J, Section J104.1 to read as follows:

J104.1. Submittal Requirements. Application for a grading permit shall be accompanied by four sets of plans and specifications, and supporting data consisting of a soils engineering report and an engineering geology report where required by the Building Official. The sets of plans submitted for final approval shall be submitted on mylar. The plans and specifications shall be prepared and signed by an individual licensed by the state to prepare such plans or specifications when required by the building official. The dates of the soils engineering and any engineering geology reports, along with the names, addresses, and phone numbers of the firms or individuals who prepared the reports, shall appear on the grading plans. In addition to the provisions of Section 105.3, Appendix Chapter 1, the applicant shall state the estimated quantities of excavation and fill.

(GG) Appendix Chapter J, Section J104.3: Amend Appendix Chapter J, Section J104.3 to read as follows:

J104.3. Soils Report. A soils report prepared by registered design professionals shall be provided which shall identify the nature and distribution of existing soils; conclusions and recommendations for grading procedures that are incorporated into the grading plans or specifications, or when approved by the building official, included by reference; soil design criteria for any structures or embankments required to accomplish the proposed grading; and, where necessary, slope stability studies, and recommendations and conclusions regarding site geology.

ARTICLE III. CALIFORNIA RESIDENTIAL CODE

SEC. 14-4. CALIFORNIA RESIDENTIAL CODE ADOPTED.

The part 2.5 of twelve parts of the California Code of Regulations, Title 24, known as the California Residential Code ("CRC"), 2010 Edition, as published by the International Code Council, 500 New Jersey Avenue, NW, 6th Floor, Washington, D.C. 20001, is hereby adopted by reference, subject to the amendments, additions, and deletions hereinafter set forth. One true copy of this code is on file in the office of the City Clerk and is available for public inspection as required by law.

SEC. 14-5. AMENDMENTS TO THE CRC.

(A) Chapter 1 Division II, Section R102.7: Amend Section R102.7 to read as follows:

R102.7. Existing structures. The legal occupancy of any structure existing on the date of adoption of this code shall be permitted to continue without change, except as is specifically covered in this code, the provisions of the Oxnard City Code, or as is deemed necessary by the building official for the general safety and welfare of the occupants and the public.

(B) Chapter 1 Division II, Section R103.1: Amend Section R103.1 to read as follows:

R103.1. Creation of enforcement agency. The Building and Engineering Division of the Development Services Department is hereby created and the official in charge thereof shall be known as the building official.

(C) Chapter 1 Division II, Section R105.2: Amend Section R105.2, items 2 and 3, to read as follows:

Building:

2. Fences not over 6 feet high and masonry walls not over 3'-6" high as measured from the lowest finished grade to the top of the wall.

3. Retaining walls that are not over 3 feet in height measured from the bottom of the footing to the top of the wall, unless supporting a surcharge or impounding Class I, II, or II-A liquids.

(D) Chapter 1 Division II, Section R105.3.2: Amend Section R105.3.2 to read as follows:

R105.3.2. Time limitation of application. An application for a permit for any proposed work shall be deemed to have been abandoned 180 days after the date of filing, unless such application has been pursued in good faith or a permit has been issued; except that the building official is authorized to grant one or more extensions of time for additional periods not exceeding 180 days each. The extension shall be requested in writing and justifiable cause demonstrated.

(E) Section R313: Amend Section R313 to read as follows:

R313. General. Approved automatic fire extinguishing systems shall be installed and maintained in accordance with Chapter 14 of the Oxnard City Code, Article XVI.

(F) Section R403.1.2: Amend Section R403.1.2 to read as follows:

R403.1.2. Continuous footing in Seismic Design Category D₂

The braced wall panels at exterior walls of buildings located in Seismic Design Category D₂ shall be supported by continuous footings. All required interior braced wall panels in buildings shall be supported by continuous footings.

(G) Section R403.1.3: Delete Exemption to Section R403.1.3.

(H) Table R602.10.1.2(2): Amend Table R602.10.1.2(2) to read as follows:

TABLE R602.10.1.2(2)^{a, b, c}
BRACING REQUIREMENTS BASED ON SEISMIC DESIGN CATEGORY
(AS A FUNCTION OF BRACED WALL LINE LENGTH)

| SOIL CLASS D ^a WALL HEIGHT = 10 FT 10 PSF FLOOR DEAD LOAD 15 PSF ROOF/CEILING DEAD LOAD BRACED W | | | MINIMUM TOTAL LENGTH (feet) OF BRACED WALL PANELS REQUIRED ALONG EACH BRACED WALL LINE | | | |
|---|---|----------------------------|--|------------------------------------|----------------------------|--------------------------------------|
| Seismic Design Category (SDC) | Story Location | Braced Wall Line Length | Method LIB, DWB, SFB, PBS, and HPS | Methods ^d GB and PCP | Method WSP ^e | Continuous Sheathing ^e |
| SCD D ₂ ^e |  | 10 | NP | 8.0 | 2.5 | 2.1 |
| | | 20 | NP | 16.0 | 5.0 | 4.3 |
| | | 30 | NP | 24.0 | 7.5 | 6.4 |
| | | 40 | NP | 32.0 | 10.0 | 8.5 |
| | | 50 | NP | 40.0 | 12.5 | 10.6 |
| |  | 10 | NP | NP | 5.5 | 4.7 |
| | | 20 | NP | NP | 11.0 | 9.4 |
| | | 30 | NP | NP | 16.5 | 14.0 |
| | | 40 | NP | NP | 22.0 | 18.7 |
| | | 50 | NP | NP | 27.5 | 23.5 |

- a. Wall bracing lengths are based on a soil site class "D." Interpolation of bracing length between the *S_d*, values associated with the seismic design categories shall be permitted when a site-specific *S_d* value is determined in accordance with Section 16
- b. Foundation cripple wall panels shall be braced in accordance with Section R602.10.9
- c. Methods of bracing shall be as described in Sections R602.1 0.2, R602.1 0.4 and R602.1 0.5
- d. Methods GB and PCP braced wall panel h/w ratio shall not exceed 1:1.
- e. Wood Structural Panel shall have a minimum thickness in SCD D₂ of 15/32", and shall not be attached using staples.

(I) Section R602.10.7.1: Amend Section R602.10.7.1 by deleting the Exception.

(J) Section R703.1: Amend Section R703.1 to read as follows:

R703.1. General. Exterior walls shall provide the building with a weather-resistant exterior wall envelope. The exterior wall envelope shall included flashing as describe in Section R703.8. Additionally, balconies, landings, exterior stairways, occupied roofs and similar surfaces exposed to the weather and sealed underneath shall be waterproofed and sloped a minimum 1/4 unit vertical in 12 units horizontal (2% slope) for drainage. The weather-exposed areas with ceilings or horizontal projections not required to be sealed for fire resistive construction shall be provided with ventilation devices so as to provide adequate air movement to dry out any moisture infiltrating within the horizontal areas. Details and notes on ventilation devices shall be provided in the submittal drawings.

(K) Section R802.10.2: Amend Section R802.10.2 to read as follows:

R802.10.2 Design. Wood trusses shall be designed in accordance with accepted engineering practice. The design and manufacture of metal-plate-connected wood trusses shall comply with ANSI/TPI 1. The truss design drawings shall be prepared by a registered professional.

(L) Section R902.1: Amend the first paragraph of Section R902.1 to read as follows:

R902.1. Roofing covering materials. The roof covering on any structure regulated by this code shall be a Class A or B roof covering. The roof covering assembly includes the roof deck, underlayment, interlayment, insulation, and covering which is assigned a roof covering classification. Roof coverings required to be listed by this section shall be tested in accordance with ASTM E 108 or UL 790. In addition, fire-retardant-treated wood roof coverings shall be tested in accordance with ASTM D 2928.

(M) Section R902.1.3: Amend Section R902.1.3 to read as follows:

R902.1.3. Roof coverings in all other areas. All reroofing shall be constructed with Class A or B roofing and shall conform to the applicable provisions of this Chapter, or as approved by the building official.

(N) Section R902.2: Amend the first paragraph of Section R902.2 to read as follows:

R902.2: Fire-retardant treated shingles and shakes. Fire-retardant treated wood shakes and shingles are wood shakes and shingles complying with UBC Standard 15-3 or 15-4 which are impregnated by the full-cell vacuum-pressure process with fire-retardant chemicals, and which have been qualified by UBC Standard 15-2 for use on Class A or B roofs.

ARTICLE IV. CALIFORNIA GREEN BUILDING STANDARDS CODE

SEC. 14-6. CALIFORNIA GREEN BUILDING STANDARDS CODE ADOPTED.

The part 2.5 of twelve parts of the California Code of Regulations, Title 24, known as the California Green Building Standards Code ("CALGreen"), 2010 Edition, including Appendices 1, C, H, I, and J, as published by the International Code Council, 500 New Jersey Avenue, NW, 6th Floor, Washington, D.C. 20001, is hereby adopted by reference, subject to the amendments, additions, and deletions hereinafter set forth. One true copy of this code is on file in the office of the City Clerk and is available for public inspection as required by law.

ARTICLE V. PROPERTY MAINTENANCE AND ABATEMENT CODES

SEC. 14-8. INTERNATIONAL PROPERTY MAINTENANCE CODE AND UNIFORM CODE FOR THE ABATEMENT OF DANGEROUS BUILDINGS ADOPTED.

The International Property Maintenance Code, 2006 Edition, and the Uniform Code for Abatement of Dangerous Buildings, 1997 Edition, as published respectively by the International Code Council, 500 New Jersey Avenue, NW, 6th Floor, Washington, D.C. 20001, and the International Conference of Building Officials, 5360 South Workman Mill Road, Whittier, California 90601, are hereby adopted by reference. One true copy of these codes is on file in the office of the City Clerk and is available for public inspection as required by law.

ARTICLE VI. CALIFORNIA HISTORICAL BUILDING CODE

SEC. 14-9. CALIFORNIA HISTORICAL BUILDING CODE ADOPTED.

The eighth part of twelve parts of the California Code of Regulations, Title 24, known as the California Historical Building Code ("CHBC"), 2010 Edition, including Appendix A, as published by the International Code Council, 500 New Jersey Avenue, NW, 6th Floor, Washington, D.C. 20001, is hereby adopted by reference. One true copy of this code is on file in the office of the City Clerk and is available for public inspection as required by law.

ARTICLE VII. CALIFORNIA ELECTRICAL CODE

SEC. 14-10. CALIFORNIA ELECTRICAL CODE ADOPTED.

The third part of twelve parts of the California Code of Regulations, Title 24, known as the California Electrical Code ("CEC"), 2010 Edition, which incorporates by reference the National Electrical Code ("NEC"), 2005 Edition, published by the National Fire Protection Association, P.O. Box 9146, Quincy, MA, 02269-9959, is hereby adopted by reference, subject to the amendments hereinafter set forth. One true copy of this code is on file in the office of the City Clerk and is available for public inspection as required by law.

SEC. 14-11. AMENDMENTS.

(A) Article 90-10: Add Article 90-10 to read as follows:

Article 90-10. Administration. The legal jurisdiction and administration of this electrical code is regulated by the administrative sections as adopted in Chapter 14, Article II of the Oxnard City Code.

ARTICLE VIII. CALIFORNIA EXISTING BUILDING CODE

SEC. 14-12. CALIFORNIA EXISTING BUILDING CODE ADOPTED.

The tenth part of eleven parts of the California Code of Regulations, Title 24, known as the California Existing Buildings Code ("CEBC"), 2010 Edition, as published by the International Code Council, 500 New Jersey Avenue, NW, 6th Floor, Washington, D.C. 20001, is hereby adopted by reference. One true copy of this code is on file in the office of the City Clerk and is available for public inspection as required by law.

ARTICLE IX. CALIFORNIA MECHANICAL CODE

SEC. 14-13. CALIFORNIA MECHANICAL CODE ADOPTED.

The fourth part of eleven parts of the California Code of Regulations, Title 24, known as the California Mechanical Code ("CMC"), 2010 Edition, and Appendices A through D thereof, and Standards contained therein, published by the International Association of Plumbing and Mechanical Officials, 5001 East Philadelphia Street, Ontario, California, 91761-2816, is hereby adopted by reference, subject to the amendment hereinafter set forth. One true copy of this code is on file in the office of the City Clerk and is available for public inspection as required by law.

SEC. 14-14. AMENDMENT.

(A) Chapter One – California General Code Provisions. Except for Sections 101.1, 101.2, and 101.3, entitled "Title," "Purpose," and "Scope," Chapter One, entitled "California General Code Provisions" is hereby deleted from the CMC. The Administrative Code as adopted in the Oxnard City Code, Chapter 14, Article II, shall apply to this Article.

ARTICLE X. CALIFORNIA REFERENCED STANDARDS CODE

SEC. 14-15. CALIFORNIA REFERENCED STANDARDS CODE ADOPTED.

The twelfth part of twelve parts of the California Code of Regulations, Title 24, known as the California Referenced Standards Code ("CRSC"), 2010 Edition, as published by the International Code Council, 500 New Jersey Avenue, NW, 6th Floor, Washington, D.C. 20001, is hereby adopted by reference. One true copy of this code is on file in the office of the City Clerk and is available for public inspection as required by law.

ARTICLE XI. CALIFORNIA PLUMBING CODE

SEC. 14-16. CALIFORNIA PLUMBING CODE ADOPTED.

The fifth part of eleven parts of the California Code of Regulations, Title 24, known as the California Plumbing Code ("CPC"), 2010 Edition, including Appendices A, B, D, I, and K thereof, and standards contained therein, published by the International Association of Plumbing and Mechanical Officials, 5001 East Philadelphia Street, Ontario, California, 91761-2816, is hereby adopted by reference, subject to the amendment hereinafter set forth. One copy of this code is on file in the office of the City Clerk and is available for public inspection as required by law.

SEC. 14-17. AMENDMENT.

(A) Chapter One – California General Code Provisions. Except for Sections 101.1, 101.2, and 101.3, entitled "Title," "Purpose," and "Scope," Chapter One, entitled "California General Code Provisions" is hereby deleted from the CPC. The Administrative Code as adopted in the Oxnard City Code, Chapter 14, Article II, shall apply to this Article.

ARTICLE XII. (RESERVED)

ARTICLE XIII. (RESERVED)

ARTICLE XIV. (RESERVED)

ARTICLE XV. FIRE CODES

SEC. 14-24. CALIFORNIA FIRE CODE ADOPTED.

The California Fire Code ("CFC") 2010 Edition, including Appendix Chapter 4, Appendix B, Appendix D, Appendix F, and Appendix H, published by the International Code Council, 4051 West Flossmoor Road, Country Club Hills, IL 60478, is hereby adopted by reference, subject to the amendments, additions, and deletions hereinafter set forth. One copy of such code is on file in the office of the City Clerk and is available for public inspection as required by law.

SEC. 14-25. AMENDMENTS.

(A) Chapter 1, Section 104.12: Add Section 104.12 to read as follows:

Attachment 1
Page 19 of 27

Section 104.12. General. When the chief finds in any building, on any premises, or on any lot or parcel combustible, hazardous or explosive materials or dangerous accumulations of rubbish; or finds unnecessary accumulations of wastepaper, boxes, shavings, or any highly flammable materials which are so situated as to endanger life or property; or finds obstructions to or on fire escapes, stairs, passageways, doors, or windows that reasonably tend to interfere with the operations of the Fire Department or the egress of the occupants of such building or premises; or finds that this code is being violated, the chief is authorized to issue orders as necessary for the enforcement of the fire prevention laws and ordinances governing the same and for the safeguarding of life and property from fire.

(B) Chapter 1, Section 104.13: Add Section 104.13 to read as follows:

Section 104.13. Stopping uses, evacuation. The chief is authorized to order an operation or use stopped, or the evacuation of any premises building or vehicle or portion thereof which has or is a fire hazard, hazardous condition or situation which presents a hazard to life or property.

(C) Section 503.2.1: Amend Section 503.2.1 to read as follows:

Section 503.2.1. Dimensions. Fire apparatus access roads shall have an unobstructed width of not less than 26 feet (7925 mm) and an unobstructed height of not less than 13 feet 6 inches (4115 mm).

Exceptions:

1. Alleys without fire hydrants must have an unobstructed width of not less than 20 feet (6096 mm).
2. Approved security gates in accordance with Section 503.6.

(D) Section 503.7: Add Section 503.7 to read as follows:

Section 503.7. Electronic and Electric Access Gates. When access to or within a structure or area is impeded by an electronically or electrically secured opening or gate, such electronically or electrically secured opening or gate shall be constructed and maintained in accordance with plans approved by the Fire Code Official or Oxnard Police Department. The Fire Code Official or Oxnard Police Department shall not approve such plans unless the plans allow emergency vehicles and emergency personnel to open such electronically or electrically secured openings or gates by City approved radio equipment used by such emergency vehicles or personnel.

On or before August 1, 2006, all existing electronically or electrically secured openings or gates that impede access to a structure or area shall either be (a) removed, or (b) constructed and maintained in accordance with plans approved by the Fire Code Official or Oxnard Police Department.

For the purposes of this section 503.7, "opening" shall be limited to an exterior door for a commercial or industrial building or a door on a commercial, industrial, or residential

property that limits access to a common area that is an accessway to more than one commercial, industrial, or residential occupancy.

(E) Section 507.5: Amend Section 507.5 to read as follows:

Section 507.5. Fire Hydrant systems. Fire hydrant systems shall comply with Sections 507.5.1 through 507.5.6 and Oxnard Fire Department published Standards or an approved method.

(F) Section 605.11: Add Section 605.11 to read as follows:

Section 605.11. Photovoltaic Systems. Photovoltaic Systems shall comply with Oxnard Fire Department published Standards and the California Office of the State Fire Marshal "Solar Photovoltaic Installation Guideline" published April 22, 2008.

(G) Section 903.4.2.1: Add Section 903.4.2.1 to read as follows:

Section 903.4.2.1. Exterior Strobe. One approved exterior strobe shall be located in an approved location.

(H) Section 906.1, item 9: Add Section 906.1, item 9, to read as follows:

9. As required by the Fire Code Official.

(I) Section 907.6.2.3.1, item 12: Add Section 907.6.2.3.1, item 12, to read as follows:

12. Approved exterior strobe, in an approved location.

(J) Section 907.4.5: Add Section 907.4.5 to read as follows:

Section 907.4.5. Fog or Smoke Emitting Systems. No system shall be installed in any building/structure or portion thereof, which discharges any gas, vapor, liquid or other product when the primary intent of system discharge is to obscure the vision, cause disorientation, or otherwise incapacitate any occupant of said building/structure or portion thereof. Nothing in this section is intended to preclude the installation of an approved fire suppression system.

(K) Section B105.1: Amend Section B105.1 to read as follows:

Section B105.1. One- and two-family dwellings. The minimum fire-flow requirements for one- and two-family dwellings shall be not less than that specified in Table B105.1.

Exception: A reduction in required fire flow of 50 percent, as approved, is allowed when the building is provided with an approved automatic fire sprinkler system.

ARTICLE XVI. FIRE SPRINKLERS

SEC. 14-25. AUTOMATIC FIRE SPRINKLER SYSTEM.

The California Fire Code ("CFC") 2010 Edition, Section 903, Automatic Sprinkler Systems, is hereby amended as follows:

(A) Section 903.2 through section 903.2.4: Amend Section 903.2 through 903.2.4 to read as follows:

903.2. Where required. Approved automatic fire sprinkler systems shall be installed in all structures, occupancies, and locations as set forth in this section. For the purposes of this section, fire walls shall not be considered as creating separate buildings.

903.2.1. Definitions.

The following words and terms shall, for the purposes of section 903.2, have the following meanings:

Bathroom. A room or compartment containing one or more of the following: a toilet, a tub, or a shower.

903.2.2. New Construction.

Automatic fire sprinkler systems shall be installed, maintained, and accessible for service in all new buildings, regardless of location, floor area, construction type, or occupancy.

Exceptions:

1. Spaces and areas in telecommunications buildings used exclusively for telecommunications equipment, associated electrical power distribution equipment, batteries and standby engines, provided those spaces or areas are equipped throughout with an automatic fire alarm system and are separated from the remainder of the building by fire barriers consisting of not less than 1-hour fire-resistance-rated walls and 2-hour fire-resistance-rated floor/ceiling assemblies.
2. Automatic fire sprinkler protection for fixed guideway transit systems shall be as per Section 903.2.17.
3. Trash enclosures that are of non-combustible construction including the roof or cover, and at least ten (10) feet from any adjacent structure, and at least five (5) feet from the nearest property line.
4. The Fire Code Official is authorized to make exception for carports, storage sheds, and similar structures having less than 500 square feet of roof area including overhangs, if the structure is least ten (10) feet from

any adjacent structure, and at least five (5) feet from the nearest property line.

5. The Fire Code Official is authorized to make exception for structures of non-combustible construction that do not have occupiable space, and that have no storage, insignificant fire load, and no exposures.

903.2.3. Existing Construction.

Automatic fire sprinkler systems shall be installed, maintained, and accessible for service throughout existing structures and additions in the following situations.

1. Whenever there is a change in occupancy in the structure or change in use classification to a higher or more hazardous occupancy or use classification based on the Building Code classifications or as determined by the Fire Code Official.
2. Except for single family residences, whenever permits for additions or alterations in a structure result in an increase of cumulative area of more than 1,000 square feet of total structure area, including mezzanines and additional stories. Additional area determination shall be cumulative, from the effective date of this ordinance.
3. For single family residences, whenever permits for additions or alterations result in an increase of cumulative area of more than 1,000 square feet of total residential structure area, including additional stories. Additional area determination shall be cumulative, from the effective date of this ordinance. Sprinkler coverage shall include the entire existing structure, garage(s), and adjacent accessory structures.
4. In rooms where nitrate film is stored or handled.
5. In protected combustible fiber storage vaults as defined in this code.

903.2.4. Reserved.

(B) Section 903.2.6 through section 903.2.10: Amend Section 903.2.6 through 903.2.10 as follows:

903.2.6. Reserved.

903.2.7. Reserved.

903.2.8. Reserved.

903.2.9. Reserved.

903.2.10. Reserved.

(C) Section 903.2.18: Amend Section 903.2.18 to read as follows:

903.2.18. Reserved.

(D) Section 903.3.1.2: Add the following sections:

903.3.1.2.2. Overhangs. Sprinkler protection is required under exterior roofs, canopies, and overhangs over four (4) feet in width.

Exceptions:

1. The Fire Code Official is authorized to make exception where the construction is non-combustible or limited combustible, and, where no combustibles are stored or handled, and the area is at least 50 percent open.

903.3.1.2.3. Under stairs. Sprinkler protection is required for usable spaces and compartments under stairs, including bathrooms and closets.

903.3.1.2.4. Attics, crawl spaces, concealed spaces. Attics, crawl spaces, and normally unoccupied concealed spaces that do not contain fuel-fired appliances do not require sprinkler coverage. In attics, crawl spaces, and normally unoccupied concealed spaces that contain fuel-fired equipment, a sprinkler shall be installed above the equipment; however, sprinklers shall not be required in the remainder of the space.

903.3.1.2.5. Ceiling obstructions. Pendant sprinklers within 3 feet of the center of a ceiling fan, surface-mounted ceiling luminaire or similar object shall be considered to be obstructed, and additional sprinklers shall be installed. Sidewall sprinklers within 5 feet of the center of a ceiling fan, surface-mounted ceiling luminaire or similar object shall be considered to be obstructed, and additional sprinklers shall be installed.

(E) Section 903.3.1.3: Add the following sections:

903.3.1.3.1. Overhangs. Sprinkler protection is required under exterior roofs, canopies, and overhangs over four (4) feet in width.

Exceptions:

1. The Fire Code Official is authorized to make exception where the construction is non-combustible or limited combustible, and, where no combustibles are stored or handled, and, the area is at least 50 percent open.

903.3.1.3.2. Under stairs. Sprinkler protection is required for usable spaces and compartments under stairs, including bathrooms and closets.

903.3.1.3.3. Attics, crawl spaces, concealed spaces. Attics, crawl spaces, and normally unoccupied concealed spaces that do not contain fuel-fired appliances do not require

sprinkler coverage. In attics, crawl spaces, and normally unoccupied concealed spaces that contain fuel-fired equipment, a sprinkler shall be installed above the equipment; however, sprinklers shall not be required in the remainder of the space.

903.3.1.3.4. Ceiling obstructions. Pendant sprinklers within 3 feet of the center of a ceiling fan, surface-mounted ceiling luminaire or similar object shall be considered to be obstructed, and additional sprinklers shall be installed. Sidewall sprinklers within 5 feet of the center of a ceiling fan, surface-mounted ceiling luminaire or similar object shall be considered to be obstructed, and additional sprinklers shall be installed.

ARTICLE XVII. (RESERVED)

ARTICLE XVIII. (RESERVED)

ARTICLE XIX. (RESERVED)

PART 4. The City Council, following due consideration, hereby finds and determines that all the amendments, deletions, and additions to the forgoing California Building Standards Code and other codes are due to the following local conditions:

(A) Climatic

1. The City experiences periods of high temperatures accompanied by low humidity and high winds each year. The City also experiences periods of intense rainfall, which creates the need for special drainage precautions. Close proximity to the ocean may accelerate some building components to erode, corrode, decay, and expose beach homes to ocean wave force and damp corrosive microclimates.

2. During the months October through March, the City experiences wind conditions known as the "Santa Ana" winds. These very strong, hot, dry northeasterly winds considerably aid the spread of fire and create a strong possibility of a conflagration in all structures during this period. During these wind conditions, much of the Fire Department's resources are used to combat life safety problems such as downed power lines. The Fire Department is forced to provide standby protection for extended periods because the electric utility is overloaded with high priority calls. The Fire Department equipment used on these non-firefighting calls is, therefore, not available for response to structure fires. Thus, even a fire in one structure not immediately extinguished such as by a fire sprinkler system could spread and cause significant property damage and/or loss of life.

3. Although there are few brush or forest areas within the City, the Fire Department receives requests for aid from jurisdictions involved in firefighting these types of fires outside the City. This response leaves the City's firefighting resources at a lower than normal level and impacts the Fire Department's ability to promptly respond to structure fires when they occur at the same time.

4. During the hot, dry wind period, the number of outside fires, such as trash and grass fires, increases dramatically. These fires do not pose a serious threat to life or property, but do occupy firefighting resources and seriously impact the Fire Department's ability to respond to structure fires when they occur at the same time.

(B) Geological

1. The City is located in close proximity to 3 major fault systems capable of producing earthquakes ranging from 6.7 to 7.3 in magnitude, and has been determined by the State of California Seismic Hazards Mapping program to be underlain by soil layers that are prone to liquefaction failure. Special seismic design, construction, and inspection considerations must be in place to provide a reasonable degree of structural integrity for buildings constructed in these areas. Additionally, the potential for multiple fires occurring simultaneously after a large seismic event will tax available firefighting resources. Built-in fire protection will assist in extinguishing or controlling fires.

2. The City is located in an area with expansive soils, high groundwater table, and ocean frontage. Special foundation considerations and soils analysis requirements must be in place to provide a reasonable degree of structural integrity for buildings constructed in these areas.

(C) Topographical

1. The City has flat land and waterfront developments that require special drainage and coastal precautions, as well as a system of roadways and highways that generate traffic noise. Structures would be subject to water damage without special requirements addressing site drainage and coastal wave and wind forces.

2. During the rainy season, from December through April, the City is subject to flooding, making various parts of the City inaccessible to firefighting equipment on short notice. This prolongs the Fire Department's response time to structure fires.

3. The City is on a flat, coastal plain, and is in a tsunami inundation zone. Additionally, many of the evacuation routes from this zone pass through the City. The arrival time of a tsunami may be predicted, but not its magnitude. Therefore, evacuation measures may be taken, but the entire area is defenseless when it strikes. During and after a tsunami, these coastal areas will not be easily accessible to firefighting and other emergency equipment.

The City Council further finds that such amendments, deletions, and additions are necessary to best serve the public health and welfare. The City Council further finds and determines that all the amendments, deletions, and additions are also required for the reasons set forth in the Index and Summary to Model Codes and Amendments, which is attached hereto and incorporated herein as Exhibit A.

PART 5. The City Attorney, who was designated to prepare a summary of this ordinance, has determined that it is not feasible to prepare a fair and adequate summary thereof. The City Council thus orders that a display advertisement of at least one quarter page containing the

information required by Government Code Section 36933(c)(2) be published in a newspaper of general circulation in the City at least five days prior to adoption of this ordinance, and another such display advertisement be similarly published within 15 days after its adoption, including the names of the Councilmembers voting for and against the ordinance.

PART 6. This ordinance was introduced for first reading on December 7, 2010, and passed on _____ 2010, by the following roll call vote and shall take effect thirty days after final passage.

PASSED AND ADOPTED this ____ day of _____ 2010, by the following vote:

AYES: Councilmembers: _____

NOES: Councilmembers: _____

ABSENT: Councilmembers: _____

Dr. Thomas E. Holden, Mayor

ATTEST:

Daniel Martinez, City Clerk

APPROVED AS TO FORM:

Alan Holmberg, City Attorney

INDEX

CALIFORNIA CODES AND AMENDMENTS

| | | |
|---------------|---|----------|
| PART 1 | Repeal, renumbering and adding of Articles of and to OCC | 1 |
| PART 2 | Acronyms | 1 |
| PART 3 | Adoption of California, International, and Uniform Codes | 3 |

ARTICLE I. (Reserved)

Section 14-1. (Reserved)

ARTICLE II. California Building Code

| | |
|--|----------|
| Section 14-2. California Building Code Adopted. | 3 |
| Section 14-3. Amendments to the CBC. | 3 |
| A. Chapter I Division II, Section 101.4.4 | 3 |
| B. Chapter I Division II, Section 103.1 | 3 |
| C. Chapter I Division II, Section 105.2 | 4 |
| D. Chapter I Division II, Section 105.3.2 | 4 |
| E. Section 903.2. Where Fire Sprinklers are Required. | 4 |
| F. Section 1403.1. Waterproofing Weather-Exposed Areas. | 4 |
| G. Section 1505.1. Roof Covering Requirements. | 4 |
| H. Section 1510.1. Re-roofing Requirements. | 5 |
| I. Section 1613.6.7. Equation 16-44. | 5 |
| J. Section 1613.8. ASCE 7 Sections 12.11.2.2.3. | 5 |
| K. Section 1613.9. ASCE 7 Table 12.8-2. | 5 |
| L. Section 1613.10. ASCE 7 Section 12.8.7. | 6 |
| M. Section 1704.4. Special Inspection for Concrete Construction. | 6 |
| N. Section 1707.3. Special Inspection of Wood Shearwalls. | 6 |
| O. Section 1710.1. Special Inspection of Wood Shearwalls. | 7 |
| P. Section 1803.2. Soils Reports. | 7 |
| Q. Section 1804.3. Drainage and Moisture Protection. | 7 |
| R. Section 1808.7.4. Foundation and Slab Elevation. | 8 |
| S. Section 1908.1. Scoping. | 8 |
| T. Section 1908.1.8. ACI 318 Section 22.10. | 8 |
| U. Section 1908.1.11. ACI 318 Sections 21.6.4.1. | 9 |
| V. Section 1908.1.12. ACI 318 Section 21.6.4.8. | 9 |
| W. Section 1908.1.13. ACI 318 Section 21.9.4.6. | 9 |
| X. Section 1908.1.14. ACI 318 Section 21.11.6. | 10 |
| Y. Section 2204.1.1. Consumables for Welding. | 10 |
| Z. Section 2205.4. AISC 341 Section 13.2f. | 10 |
| AA. Section 2306.2.1. Wood Structural Panel Diaphragms. | 10 |
| BB. Section 2306.3. Wood Structural Panel Shear Walls. | 11 |

EXHIBIT A - INDEX AND SUMMARY TO THE CALIFORNIA CODES AND AMENDMENTS

| | | |
|-----|---|----|
| CC. | Section 2306.7. Shear Walls of Other Materials. | 11 |
| DD. | Appendix Chapter J, Section J103.2, Exception 1 | 12 |
| EE. | Appendix Chapter J, Section J103.2, Exception 8 | 12 |
| FF. | Appendix Chapter J, Section J104.1 | 12 |
| GG. | Appendix Chapter J, Section J104.3 | 13 |

ARTICLE III. California Residential Code

| | | |
|----------------------|--|----|
| Section 14-4. | California Residential Code Adopted. | 13 |
| Section 14-5. | Amendments to the California Residential Code. | 13 |
| A. | Chapter I Division II, Section R102.7 | 13 |
| B. | Chapter I Division II, Section R103.1 | 14 |
| C. | Chapter I Division II, Section R105.2 | 14 |
| D. | Chapter I Division II, Section R105.3.2 | 14 |
| E. | Section R313. Fire Sprinklers Required. | 14 |
| F. | Section R403.1.2. Continuous Footing in Seismic Design Category D ₂ . | 14 |
| G. | Section R403.1.3. Delete Exemption to Continuous Footing Requirement | 14 |
| H. | Table R602.10.1.2(2). Bracing Requirements Based on Seismic Design Category. | 15 |
| I. | Section R602.10.7.1. Braced Wall panel Support. | 15 |
| J. | Section R703.1. Water Proofing. | 15 |
| K. | Section R802.10.2. Truss Design. | 15 |
| L. | Section R902.1. Roof Covering Materials. | 15 |
| M. | Section R902.1.3. Roof Coverings in all other areas. | 15 |
| N. | Section R902.2. Fire-retardant treated shingles and shakes. | 15 |

ARTICLE IV. California Green Building Standards Code

| | | |
|----------------------|--|----|
| Section 14-6. | California Green Building Standards Code Adopted. | 15 |
|----------------------|--|----|

ARTICLE V. Property Maintenance and Abatement Codes

| | | |
|----------------------|---|----|
| Section 14-8. | International Property Maintenance Code and Uniform Code for the Abatement of Dangerous Buildings Adopted. | 16 |
|----------------------|---|----|

ARTICLE VI. California Historical Building Code

| | | |
|----------------------|---|----|
| Section 14-9. | California Historical Building Code Adopted. | 16 |
|----------------------|---|----|

EXHIBIT A - INDEX AND SUMMARY TO THE CALIFORNIA CODES AND AMENDMENTS

ARTICLE VII. California Electrical Code

| | |
|---|----|
| Section 14-10. California Electrical Code Adopted. | 16 |
| Section 14-11. Amendment. | 16 |

ARTICLE VIII. California Existing Buildings Code

| | |
|---|----|
| Section 14-12. California Existing Buildings Code Adopted. | 17 |
|---|----|

ARTICLE IX. California Mechanical Code

| | |
|---|----|
| Section 14-13. California Mechanical Code Adopted. | 17 |
| Section 14-14. Amendment. | 18 |

ARTICLE X. California Referenced Standards Code

| | |
|---|----|
| Section 14-15. California Referenced Standards Code Adopted. | 18 |
|---|----|

ARTICLE XI. California Plumbing Code

| | |
|---|----|
| Section 14-16. California Plumbing Code Adopted. | 18 |
| Section 14-17. Amendment. | |

ARTICLE XII. (RESERVED)

ARTICLE XIII. (RESERVED)

EXHIBIT A - INDEX AND SUMMARY TO THE CALIFORNIA CODES AND AMENDMENTS

ARTICLE XIV. (RESERVED)

ARTICLE XV. Fire Codes

| | |
|---|----|
| Section 14-24. California Fire Code Adopted. | 19 |
| Section 14-25. Amendments. | 19 |
| A. Section 104.12 | 19 |
| B. Section 104.13 | 20 |
| C. Section 503.2.1 | 20 |
| D. Section 503.7 | 20 |
| E. Section 507.5 | 20 |
| F. Section 605.11 | 20 |
| G. Section 903.4.2.1 | 21 |
| H. Section 906.1 | 21 |
| I. Section 907.6.2.3.1 | 21 |
| J. Section 907.4.5 | 21 |
| K. Section B105.1 | 21 |

ARTICLE XVI. Fire Sprinklers

| | |
|--|----|
| Section 14-26. Automatic Fire Sprinkler System. | 21 |
| A. Section 903.2 through 903.2.4 | 21 |
| B. Section 903.2.6 through 903.2.10 | 23 |
| C. Section 903.2.1.2 | 23 |
| D. Section 903.3.1.2 | 24 |

ARTICLE XVII. (RESERVED)

ARTICLE XVIII. (RESERVED)

ARTICLE XIX. (RESERVED)

EXHIBIT A - INDEX AND SUMMARY TO THE CALIFORNIA CODES AND AMENDMENTS

| | | |
|---------------|-------------------------|----|
| PART 4 | General Findings | 24 |
| PART 5 | Publication | 26 |
| PART 6 | Effective Date | 26 |

SUMMARY

PART 3

**ARTICLE II.
CALIFORNIA AND BUILDING CODE**

Section 14-2 References the adoption of the California Building Code, 2007 Edition.

Section 14-3 Amendments to the CBC.

A. **Chapter 1 Division II, Section 101.4.4.** Corrects an inaccurate administrative reference.

Finding of Need: Administrative.

B. **Chapter 1 Division II, Section 103.1.** Administrative clarification of terminology.

Finding of Need: Administrative.

C. **Chapter 1 Division II, Section 105.2** Clarifies restrictions on items exempt from permits.

Finding of Need: Local Climactic Condition #1, Local Geological Conditions #1 and #2.

D. **Chapter 1 Division II, Section 105.3.2.** Modifies the time limit of permit extensions granted by the Building Official.

Finding of Need: Administrative.

EXHIBIT A - INDEX AND SUMMARY TO THE CALIFORNIA CODES AND AMENDMENTS

- E. **Section 903.2. Where Fire Sprinklers are Required.** This amendment provides cross-reference to the Oxnard Fire Code relating to more restrictive requirements for automatic fire sprinkler systems.

Finding of Need: Editorial reference.

- F. **Section 1403.1. Waterproofing Weather-Exposed Areas.** Due to climatic conditions caused by the close proximity to the ocean, there is a specific need to ventilate certain areas of a building which are more clearly addressed in this amendment.

Finding of Need: Local Climatic Condition #1

- G. **Section 1505.1. Roof Covering Requirements.** Amends the CBC to be consistent with Fire Prevention Program regulations for roof covering requirements of Class A or B roofing.

Finding of Need: Local Topographic Condition #2 and Local Climatic Conditions #'s 1,2,3, and 4 to assure public health and welfare.

- H. **Section 1505.10.1. Re-roofing Requirements.** Amends the CBC to be consistent with Fire Prevention Program regulations for roof covering requirements of Class A or B roofing.

Finding of Need: Local Topographic Condition #2 and Local Climatic Conditions #'s 1,2,3, and 4 to assure public health and welfare.

- I. **Section 1613.6.7. Equation 16-44.** The inclusion of the importance factor in this equation has the unintended consequence of reducing the minimum seismic separation distance for important facilities such as hospitals, schools, assembly occupancies, and other important structures.

Finding of Need: Local Geological Condition #1.

- J. **Section 1613.8, ASCE 7 Section 12.11.2.2.3.** The revision to section 12.11.2.2.3 of ASCE 7-05 strengthens and clarifies the requirements for anchorage of concrete and masonry bearing walls to wood roofs, and is intended to increase life safety by preventing failures observed in recent past earthquakes.

Finding of Need: Local Geological Condition #1.

EXHIBIT A - INDEX AND SUMMARY TO THE CALIFORNIA CODES AND AMENDMENTS

- K. **Section 1613.9. ASCE 7-05 Table 12.8-2.** The steel Buckling Restrained Braced Frame (BRBF) system was first approved for use in the 2003 NEHRP Provisions. The values for the approximate period perimeters C_t and x were also approved as part of that original BSSC Proposal 6-6R (2003). It was an oversight that these parameters were not carried forward into the 2005 Edition of the ASCE7. Currently these two factors can be found in Appendix R of AISC 341-05. There, they function only as a placeholder that will be removed in the next version upon approval by ASCE 7 Task Committee on Seismic.

Finding of Need: Local Geological Condition #1.

- L. Section 1613.10, Equation 12.8-16 of ASCE 7 Section 12.8.7
The revision to this Table corrects an oversight while transcribing it from NEHRP Provisions (2003) equation 5.2-16. This is consistent with the provisions adopted by OSHPD and DSA-SS as reflected in Section 1615.10.5 of the code.

Finding of Need: Local Geological Condition #1.

- M. **Section 1704.4. Special Inspection for Concrete Construction.** This provision limits the types of concrete construction elements that can be installed without deputy inspection and is intended to increase quality control of critical structural elements.

Finding of Need: Local Geological Conditions #1 and #2.

- N. **Section 1707.3. Special Inspection of Wood Shearwalls.** Allows for an exemption to special inspection of wood shearwalls if compensating design and construction limitations are observed.

Finding of Need: Local Geological Conditions #1.

- O. **Section 1710.1. General.** It is important to recognize that the registered design professional responsible for the structural design has thorough knowledge of the building being constructed. This design professional has a clear understanding of the importance of the major structural elements and connections that affect the vertical and lateral load resisting system of the structure. Additional requirements are provided to help clarify the role and duties of the structural observer and the method of reporting and correcting observed deficiencies to the building official.

Finding of Need: Local Geological Conditions #1.

EXHIBIT A - INDEX AND SUMMARY TO THE CALIFORNIA CODES AND AMENDMENTS

- P. **Section 1803.2. Investigations required.** Due soil conditions observed, special soils investigations are required.

Finding of Need: Local Climactic Condition #1, Local Topographical Condition #1.

- Q. **Section 1804.3. Drainage and Moisture Protection.** Due to the relatively flat topography of the City, additional drainage and moisture protection requirements required.

Finding of Need: Local Climactic Condition #1, Local Topographical Condition #1.

- R. **Section 1808.7.4. Drainage and Moisture Protection.** Due to the relatively flat topography of the City, additional drainage and moisture protection requirements required.

Finding of Need: Local Climactic Condition #1, Local Topographical Condition #1.

- S. **Section 1908.1. Scoping.** Modifies the references to subsequent code sections so as to be consistent with other local code modifications contained herein.

Finding of Need: Administrative clarification relating to the scoping of this section.

- T. **Section 1908.1.8. ACI 318 Section 22.10.** Amends this section to limit the use of unreinforced or under-reinforced concrete in areas of high seismic activity so as to protect building structures and occupants from unnecessary damage.

Finding of Need: Local Geological Conditions #1 and #2.

- U. **Section 1908.1.11. ACI 318 Section 21.6.4.1.** Carries over important provisions relating to the design of concrete columns and beams that resist seismic loads from previous codes.

Finding of Need: Local Geological Condition #1.

- V. **Section 1908.1.12. ACI 318 Section 21.6.4.8.** Carries over important provisions relating to the design of concrete columns and beams that resist seismic loads from previous codes.

EXHIBIT A - INDEX AND SUMMARY TO THE CALIFORNIA CODES AND AMENDMENTS

Finding of Need: Local Geological Condition #1.

- W. **Section 1908.1.13. ACI 318 Section 21.9.4.6.** Carries over important provisions relating to the design of heavily loaded concrete walls that resist seismic loads from previous codes.

Finding of Need: Local Geological Condition #1.

- X. **Section 1908.1.14. ACI 318 Section 21.11.6.** Section modified to provide enhanced performance for certain structural elements of concrete floor and roof slabs based on observations from the Northridge Earthquake.

Finding of Need: Local Geological Condition #1.

- Y. **Section 2204.1.1. Section 2204.1.1.** Update to current knowledge the AISC 341-05, both of these amendments have been adopted by Division of State Architect Structural Safety Section and OSHPD for work in the medical facilities.

Finding of Need: Local Geological Condition #1.

- Z. **Section 2205.4 AISC 341, Part I, Section 13.2 Members.** Past test results on braces used in steel concentrically braced frames (SCBF) indicated that many commonly used sections and brace configurations do not meet seismic performance expectations. Square and rectangular cross-section HSS were shown to be particularly susceptible to fracture due to local buckling behavior of the cross section and, therefore, are not recommended by Structural Engineers Seismology and Steel Committee. This is the recommendation of the Structural Committees studying this frame type.

Finding of Need: Local Geological Condition #1.

- AA. **Section 2306.2.1. Wood Structural Panel Diaphragms.** Provides additional restrictions for wood structural diaphragms in areas of high seismic activity.

Finding of Need: Local Geological Condition #1.

- BB. **Section 2306.3. Wood Structural Panel Shear Walls.** Provides additional restrictions for wood structural shear walls in areas of high seismic activity.

EXHIBIT A - INDEX AND SUMMARY TO THE CALIFORNIA CODES AND AMENDMENTS

Finding of Need: Local Geological Condition #1.

CC. **Section 2306.7. Shear Walls of Other Materials.** Provides additional restrictions on the use of drywall and stucco as seismic resisting materials for structural shear walls in areas of high seismic activity.

Finding of Need: Local Geological Condition #1.

DD. **Appendix Chapter J, Section J103.2, Exception 1.** The City is very flat and there is a concern for safe drainage design; therefore, the exemptions for a grading permit were limited 150 cubic yards of earth.

Finding of Need: Local Topographical Condition #1.

EE. **Appendix Chapter J, Section J103.2, Exception 8.** The City is very flat and there is a concern for safe drainage design; therefore, the exemptions for a grading permit were further clarified by limitations on cut depth, slope, and drainage course proximity.

Finding of Need: Local Topographical Condition #1.

FF. **Appendix Chapter J, Section J104.1.** Clarifies grading plan submittal requirements including final submittal media, supporting reports, number of sets, and earthwork estimate requirements.

Finding of Need: Administrative.

GG. **Appendix Chapter J, Section J104.3** Clarifies that the soils report recommendations for grading procedures either be incorporated into the grading plans, or by reference when approved by the Building Official.

Finding of Need: Administrative.

**ARTICLE III.
CALIFORNIA RESIDENTIAL CODE**

Section 14-4. References adoption of the California Residential Code, 2010 Edition.

Section 14-5. Amendments to the California Residential Code.

EXHIBIT A - INDEX AND SUMMARY TO THE CALIFORNIA CODES AND AMENDMENTS

- A. **Chapter 1 Division II, Section R102.7.** Corrects an inaccurate administrative reference.

Finding of Need: Administrative.

- B. **Chapter 1 Division II, Section R103.1.** Administrative clarification of terminology.

Finding of Need: Administrative.

- C. **Chapter 1 Division II, Section R105.2** Clarifies restrictions on items exempt from permits.

Finding of Need: Local Climactic Condition #1, Local Geological Conditions #1 and #2.

- D. **Chapter 1 Division II, Section R105.3.2.** Modifies the time limit of permit extensions granted by the Building Official.

Finding of Need: Administrative.

- E. **Section R313. Where Fire Sprinklers are Required.** This amendment provides cross-reference to the Oxnard Fire Code relating to more restrictive requirements for automatic fire sprinkler systems.

Finding of Need: Editorial reference.

- F. **Section R403.1.2. Continuous footing in Seismic Design Category D₂.** This amendment provides cross-reference to the Oxnard Fire Code relating to more restrictive requirements for automatic fire sprinkler systems.

Finding of Need: Local Geological Conditions #1 and #2.

- G. **Section R403.1.3. Seismic reinforcing₂.** This amendment provides a continuous footing under all braced wall lines. Due to observed performance issue during the Northridge earthquake this sections address the drift and deflection cause by lack of a continuous footing.

Finding of Need: Local Geological Conditions #1 and #2.

H. **Table R602.10.7.1. Bracing Requirements Based on Seismic Design Category.**

Cleans up the table being California does not allow three stories conventional framing and Oxnard is composed of entirely Seismic Design Category D₂ per the Residential Code. Poor performance of the diagonal wood boards, structural fiberboard sheathing, gypsum board, particle board sheathing, portland cement plaster, and hardboard panel siding, during the Northridge earthquake justifies reduction or removal of these values. Limited cyclic testing provided to the ICC Los Angeles Chapter Structural Code Committee shows that stapled wood structural shear panels do not exhibit the same behavior as the nailed wood structural shear panels.

Finding of Need: Local Geological Conditions #1 and #2.

I. **Section R602.10.7.1. Braced Wall Line Support for Seismic Design Category D₂.**

Removes an exception that allowed shear walls to be constructed without continuous foundations. This also is constant with modifications in the Building Code.

Finding of Need: Local Geological Conditions #1 and #2.

J. **Section R703.1. Waterproofing Weather-Exposed Areas.** Due to climatic conditions caused by the close proximity to the ocean, there is a specific need to ventilate certain areas of a building which are more clearly addressed in this amendment.

Finding of Need: Local Climatic Condition #1

K. **Section R802.10.2. Design.** Wood trusses are engineered structural elements that require engineered design and calculations. This amendment provides clarifications that all wood truss design draws are to be prepared by registered professional.

Finding of Need: Local Climatic Condition #1.

L. **Section R902.1. Roofing covering materials.** Amends the CRC to be consistent with Fire Prevention Program regulations for roof covering requirements of Class A or B roofing.

Finding of Need: Local Topographic Condition #2 and Local Climatic Conditions #'s 1,2,3, and 4 to assure public health and welfare.

M. **Section R902.1.3. Roof coverings in all other areas.** Amends the CRC to be consistent with Fire Prevention Program regulations for roof covering requirements of Class A or B roofing.

EXHIBIT A - INDEX AND SUMMARY TO THE CALIFORNIA CODES AND AMENDMENTS

Finding of Need: Local Topographic Condition #2 and Local Climatic Conditions #'s 1,2,3, and 4 to assure public health and welfare.

- N. **Section R902.2. : Fire-retardant treated shingles and shakes..** Amends the CRC to be consistent with Fire Prevention Program regulations for roof covering requirements of Class A or B roofing.

Finding of Need: Local Topographic Condition #2 and Local Climatic Conditions #'s 1,2,3, and 4 to assure public health and welfare.

**ARTICLE VII.
CALIFORNIA ELECTRICAL CODE**

**Section 14-10. References adoption of the California Electrical Code, 2007 Edition.
Section 14-11 Amendments to the California Electrical Code.**

- A. **Article 90-10.** The administrative provisions for the CEC shall be those in Articles I and II of this chapter.

Finding of Need: Administrative.

**ARTICLE IX.
CALIFORNIA MECHANICAL CODE**

**Section 14-13. References adoption of the California Mechanical Code, 2007 Edition.
Section 14-14. Amendments to the California Mechanical Code.**

- A. **Chapter One – General Code Provisions.** The administrative provisions for the CMC shall be those in Articles I and II of this chapter.

Finding of Need: Administrative.

**ARTICLE XI.
CALIFORNIA PLUMBING CODE**

**Section 14-16 References adoption of the California Plumbing Code, 2007 Edition.
Section 14-17 Amendments to the California Plumbing Code.**

- A. **Chapter One – General Code Provisions.** The administrative provisions for the CPC shall be those in Articles I and II of this chapter.

Finding of Need: Administrative.

**ARTICLE XV.
FIRE CODES**

Section 14-24. References Adoption of the California Fire Code, 2010 Edition.

Section 14-25. Amendments to the California Fire Code.

A. **Chapter 1, Section 104.12.** This amendment allows the Fire Code Official to issue orders with regard to a lot or parcel if there exists a fire hazard thereon.

Finding of Need: Administrative.

B. **Chapter 1, Section 104.13.** Stopping uses, evacuation. This addition allows the Fire Code Official to stop a use or order an evacuation if there is a hazardous condition or situation representing a hazard to life or property.

Finding of Need: Administrative.

C. **Section 503.2.1. Dimensions.** This amendment allows the Fire Code Official to set requirements consistent with the current operational requirements of the Fire Department's apparatus, and facilitates timely response of available apparatus.

Finding of Need: Administrative, Climatic #2, #3, Topographical #2, #3.

D. **Section 503.7. Electronic and Electric Access Gates.** This section updates exist City Code requirements regarding electronic and electric gates controls so that they reference current Fire Code sections. This section facilitates timely response of available apparatus.

Finding of Need: Administrative, Climatic #2, #3, Topographical #2, #3

E. **Section 507.5. Fire Hydrant systems.** This amendment allows the Fire Code Official to set requirements consistent with the current operational requirements of the Fire Department's apparatus.

Finding of Need: Administrative.

F. **Section 605.11. Photovoltaic Systems.** This section adopts policies published by the State Fire Marshal as code requirements. These requirements allows for fire fighting personnel to safely access all areas of the roof to provide heat ventilation and most efficient tactics to fight fire within structures.

EXHIBIT A - INDEX AND SUMMARY TO THE CALIFORNIA CODES AND AMENDMENTS

Finding of Need: Administrative, Climatic #2, #3, Topographical #2, #3

G. Section 903.4.2.1 Exterior Strobe. This requirement facilitates fire fighting personnel in locating the correct building in alarm more quickly, especially in inclement conditions. .

Finding of Need: Administrative, Climatic #2, #3, Topographical #2, #3

H. Section 906.1, #9. General. This amendment allows the Fire Code Official discretion in dealing with the placement of fire extinguishers in high theft areas.

Finding of Need: Administrative.

I. Section 907.6.2.3.1, item 12. The requirement for an exterior strobe facilitates fire fighting personnel in locating the correct building in alarm more quickly, especially in inclement conditions..

Finding of Need: Administrative, Climatic #2, #3, Topographical #2, #3

J. Section 907.4.5. Fog or Smoke Emitting Systems. The requirement provides for fire fighting personnel protection and facilitates more rapid response to building interiors for fire fighting..

Finding of Need: Administrative, Climatic #2, #3, Topographical #2, #3

K. Section B105.1. One- and two-family dwellings. This ensures that sufficient water is available for fire fighting, in concordance with fire department operational guidelines and water department operational guidelines.

Finding of Need: Administrative, Climatic #2, #3, Topographical #2, #3

**ARTICLE XVI.
FIRE SPRINKLERS**

Section 14-26. Fire Sprinklers. This section adopts modifications to the California Fire Code relating to Fire Sprinkler Requirements.

EXHIBIT A - INDEX AND SUMMARY TO THE CALIFORNIA CODES AND AMENDMENTS

A. **Sections 903.2 through 903.2.4.** This amendment updates existing City Code requirements regarding fire sprinkler systems so that they reference the correct current Fire Code sections, clarifies language, and changes the threshold requirements for residential addition areas requiring fire sprinkler systems.

Finding of Need: Administrative; Climatic #2, #3, #4; Geological #2; Topographical #2, #3.

B. **Sections 903.2.6 through 903.2.10.** This amendment updates existing City Code requirements regarding fire sprinkler systems so that they reference the correct current Fire Code sections, clarifies language, and changes the threshold requirements for residential addition areas requiring fire sprinkler systems.

Finding of Need: Administrative; Climatic #2, #3, #4; Geological #2; Topographical #2, #3.

C. **Section 903.2.18.** This amendment updates existing City Code requirements regarding fire sprinkler systems so that they reference the correct current Fire Code sections, clarifies language, and changes the threshold requirements for residential addition areas requiring fire sprinkler systems.

Finding of Need: Administrative; Climatic #2, #3, #4; Topographical #2, #3.

D. **Section 903.3.1.2.** This amendment updates existing City Code requirements regarding fire sprinkler systems so that they reference the correct current Fire Code sections, and clarifies the threshold requirements for residential fire sprinkler system coverage.

Finding of Need: Administrative; Climatic #2, #3, #4; Topographical #2, #3.

E. **Section 903.3.1.3.** This amendment updates existing City Code requirements regarding fire sprinkler systems so that they reference the correct current Fire Code sections, and clarifies the threshold requirements for residential fire sprinkler system coverage..

Finding of Need: Administrative; Climatic #2, #3, #4; Geological #2; Topographical #2, #3.